



**CAUTION** 500 VOLTS AVAILABLE. DISCONNECT POWER SUPPLY BEFORE SERVICING AND ALLOW 30 SECONDS MINIMUM FOR BLEEDERS TO DISSIPATE B+ VOLTAGES.

**TEST DATA**

(MV) DENOTES TYPICAL 1KHz SIGNAL FOR 10 WATTS OUTPUT  
 (A) INSERT BLANK PLUG INTO INPUT JACK FOR THIS TEST.  
 CONTROL SETTINGS— EQUALIZERS AT MID POSITION.  
 PRESENCE AT MINIMUM.  
 OTHERS AT MAXIMUM.

XA—USE 0.1MFD 600V CAPACITOR IN SERIES WITH GENERATOR.  
 D.C. VOLTAGES READ WITH NO SIGNAL INPUT.

FENDER MUSICAL INSTRUMENTS  
 CBS MUSICAL INSTRUMENTS  
 A DIVISION OF CBS INC.  
 FULLERTON CALIFORNIA  
 U.S.A.

- 3. USED IN SOME VERSION.
  - 2. ALL RESISTORS ARE 1/2W, 10%.
  - 1. ALL CAPACITORS AT LEAST 600 V.D.C.
- NOTES: UNLESS OTHERWISE SPECIFIED

**Fender / Rosen / Rhodes**  
 ONE HUNDRED SEVENTEEN - A DIVISION OF CBS INC.  
 FULLERTON, CALIFORNIA 92630

— SCHEMATIC —  
 180W STUDIO BASS

PART NO. 013606 REV A